



### Aratro reversibile

- Per trattori da **15-25 HP** (11-18 kW)
- Parti soggette a sforzi in acciaio trattato



### Reversible plough

- For **15-25 HP** tractors (11-18 kW)
- Parts subject to efforts in hardened steel



### Charrues réversible

- Pour tracteurs de **15-25 HP** (11-18 kW)
- Pièces soumises à des contraintes en acier trempé

mod.  
**PO**



**M**



cm



HP/Kw



Kg

11.01.07	PO 210 8"	96 x 62 x 78	15-25/11-19	78
11.01.08	PO 230 9"	96 x 62 x 88	15-25/11-19	81
11.01.09	PO 254 10"	96 x 62 x 95	25-35/18-26	85



### Aratro trivomere e quadrivomere

- Ampiezza del solco: 200 mm, 250 mm, 250 mm, 270 mm
- Profondità di aratura: 180/250 mm



### Three and four furrows plow

- Width of groove: 200 mm, 250 mm, 250 mm, 270 mm
- Depth of plowing: 180/250 mm



### Charrues avec trois et quatre charrues

- Largeur du sillon gorge: 200 mm, 250 mm, 250 mm, 270 mm
- Profondeur de travail: 180/250 mm

mod.  
**J**



**M**



HP/Kw



Kg

11.03.20	J3 20	20-25/14-18	100
11.03.25	J3 25	35-40/26-29	160
11.04.25	J4 25	40-50/29-37	195
11.04.27	J4 27	55-80/41-59	200